SAVER **ONE** SERIES
the new generation

Saver One®

AED series
MADE in ITALY

life is a breath,
...keep it safe with us

ami.italia
medical products

North Italy
Office
Viale Gran Sasso, 11
20131 Milano - Italy
Tel: +39.02.20509246
Fax: +39.02.29520839

www.amiitalia.com

South Italy
Office & Production
Via Cupa Reginella, 15
80010 Quarto - Italy
Tel: +39.081.8060574
Fax: +39.081.8764769

info@amiitalia.com

CE
0051

IMQ mark for
Safety & Quality

ami.italia
medical products

SaverOne®
everywhere for life

Sudden Cardiac Arrest can happen anytime, anywhere and without warning.
The person affected has only few precious minutes left for a chance of survival.

YOUR FIRST AID COULD BE SOMEBODY'S LAST CHANCE

SAVER ONE AEDs are designed for a public access use and licensed to administer fast and safe rescues.
Highly-effective and user-friendly for any lay rescuer, even without minimal training.

SAVER ONE Semi and Fully Automatic defibrillators are two dependable members of our AED family.
The Fully Automatic administers a defibrillating shock (when appropriate) with no shock button
for the user to press while the Semi-Automatic administers a shock at the press of a button.

Choose the best portable AED that's right for you to save lives everywhere in any public circumstance
(home, office, school, hotel, airport, train, beach, gym, pool, disco, etc.) and before EMS team arrives.

Automated testing to vouch daily functionality

A **new look** complete with all pictograms which light up necessary to guide rescuers step by step

More alternatives for recording and transfer data **internal memory**, removable **card**, **USB**

Slight yet solid with **long-lasting battery options** to ensure the best portability in any circumstance

Biphasic technology **up to 360J energy**

Unique features combined with available configurations give rise to exclusive devices

Meet AHA/ERC 2010 Guidelines

SEMI-AUTOMATIC
two buttons

FULLY AUTOMATIC
one button

SaverOne®

Maintenance-Free: Automatically performs daily, monthly and six-month extensive self-checks of all main components: battery, internal electronics, energy charge and disarm, shock and ECG calibration systems. Daily testing data are stored by the device as text file (named AED1LOG) easily readable by any computer.
AED runs further tests after each battery insertion as well as every time the device is turned on.
A visual cue (green/red status indicator) provides effective alert to users whether AED is in working order and ready for a rescue.

Helpful Text Screen: The mini LCD screen always displays a battery gauge with its residual percentage charge and runs text in tandem with audible voice instructions, helpful in noisy and chaotic environments.

Synergic "INFO" Button: The *i* button provides valuable device or battery technical information to users and is serviceable for changing the language.

CPR Coaching: More instructive voice and text prompts guide user through rescue. A built-in metronome assist responder during the CPR, providing audio cues for the appropriate number and rate of chest compressions.

Adult / Child Capability: Can be used on patients of any age with flashing icons on the keyboard providing information on the pads in use. Device senses when Pediatric pads are installed and adjusts to use a more appropriate lower energy level (50J).

DEFIBRILLATOR

Operation:	Semi-Automatic Version Fully Automatic Version
Energies:	Standard max 200J or Power max 360J
Waveform:	Adaptive BTE (biphasic truncated exponential) conforming to patient chest's impedance
Energy type:	Escalating from 50 to 360J
Protocols:	Various adult shock protocols available on request
Factory default:	Adult Standard escalating 150, 200, 200J Adult Power escalating 200, 250, 360J Pediatric (Standard or Power) 50J fixed
Charging time:	⩽9 seconds with a new and fully charged battery. Depleted battery will result in a longer charging time
Analysis time:	EN 60601, from 4 to 15 seconds
Impedance:	20-200 ohms
Sensitivity:	EN 60602-2-4 (AHADB, MITDB source), 97%
Specificity:	EN 60602-2-4 (AHADB, MITDB source), 99%
Controls:	2 buttons for Semi-Automatic: ON/OFF switch, Shock 1 button for Fully Automatic: ON/OFF switch
Flashing Icons:	"pads" warning on pads (not/not well connected) "adult/child" informing on pads type in use "don't touch patient" warning to stay clear "touch patient" informing it's safe to touch
Indicators:	Status LED indicator informing on device condition Battery gauge with remaining capacity rate Audible alerts and text display with service alarms
Upgradeable:	Can be upgraded in the field through a USB cable or a removable card whenever protocols change

BATTERY OPTIONS

Type:	Li-SOCI2 Disposable, code SAV-C0903
Autonomy:	300 complete rescue cycles (shocks at 200J and CPR) or 200 complete rescue cycles (shocks at 360J and CPR) or 35 hours ECG Monitoring for a new and fully charged battery (*)
Shelf-Life:	8 years when stored in its original packaging (*)
Standby-Life:	5 years once installed to AED, assuming one battery insertion test and daily self-tests but without switching AED on (*)
Type:	Li-Ion Accumulator (rechargeable), code SAV-C0011
Recharging time:	2,5 hours with the charger station code SAV-C0014 (*)
Autonomy:	250 shocks at 200J or 150 shocks at 360J or 21 hours in ECG Monitoring for a new fully charged battery (*)
Shelf-Life:	2,5 years or 300 charging cycles (*)

PADS OPTIONS

Type:	Disposable, pre-gelled and self-adhesive
Adult:	Preconnected code SAV-C0846, for patient >8 years or >25Kg 81 cm² conductive surface
Pediatric:	Code SAV-C0016 for patient from 1 to 8 years old or <25Kg 31 cm² conductive surface
Cable lenght:	120 cm
Shelf-Life:	30 months

EVENT RECORDING

Internal memory:	1Gbit (128 MB)
Memory capacity:	6 hours of audio, ECG and event
Optional memory:	Removable SD card. Length of storage depends on card capacity: a 2GB card records up to 100 hours
Data recording:	"AED1LOG" text file with detailed self-test activity "AEDFILES" with complete recorded events
Event review:	"Saver View Express" data management software

PHYSICAL

Size:	26,5 x 21,5 x 7,5 cm
Weight:	1,95 kg with disposable battery 2,10 kg with rechargeable battery

ENVIRONMENTAL

Operating temperature:	0º C to 55º C
Storing/Shipping temperature:	-35º C to 60º C (without battery)
Humidity:	0% to 95% relative humidity non-condensing
Sealing (IP Protection):	IEC 60529 class IP54; slash proof, dust protected
Shock/Drop Abuse Endurance:	IEC/EN 60601-1 clause 21; 1 meter drop, impact, force, rough handling, mobile tolerance
Electrostatic Discharge:	EN 61000-4-2
Electromagnetic Compatibility:	EN 60601-1-2; Emission, Immunity
Electrical Protecion:	EN 60601-1 class I type BF
EC Directive:	Class IIb

(*) Temperature at 20º C

MODEL NUMBERS

Code SVO-B0001: Semi-Automatic Standard Version at 200J
Code SVO-B0002: Semi-Automatic Power Version at 360J

Code SVO-B0847: Fully Automatic Standard Version at 200J
Code SVO-B0848: Fully Automatic Power Version at 360J

CONFIGURATION OPTIONS (Box Contents)

Conf-Norm: Standard Basic Configuration
(adult pads, disposable battery, carrying case)
Conf-Rech: Rechargeable Configuration
(adult pads, accumulator, charger station, carrying case)

6 YEARS WARRANTY

Manufactured in Italy

IMQ mark for Safety & Quality

CE 0051

11.A1/2013

SaVer One D®

the AED **goes beyond**

SAVER ONE D is a rugged, small and lightweight AED with ECG Monitoring capability.
Totally reliable for trained users featuring advanced capacities to help improve lifesaving outcomes.

THE RIGHT CHOICE FOR HARSH, OUTDOOR OR MOBILE USE

While in AED mode, it allows the user to view the ECG and everything needed to know about the patient and ongoing rescue treatment on a very large (12x8 cm) full-color interactive display. Additionally the SAVER ONE D can be switched in a ECG Monitoring mode, to allow for watch over the rhythm and heart rate while using defibrillation pads or standard ECG electrodes connected to a separate cable.

Practical and flexible with Advanced PBLS feature enabling healthcare providers to use the 15:2 CV ratio when performing a Pediatric Basic Life Support, as required by Guidelines if more than one rescuer with a duty to respond.

Great graphical interface in tandem with instructive voice prompts to guide rescuers

Functionality ensured by **automatic daily self-test**

Slight yet solid with **long-lasting battery options** to ensure the best portability in any circumstance

More alternatives for recording and transfer data **internal memory**, removable **card**, **USB**, and **IrDA Port** optional with Print Configuration

Biphasic technology **up to 360J energy**

Unique features combined with available configurations give rise to exclusive devices

Meet AHA/ERC 2010 Guidelines

SaVer One D®

AED
ECG Monitoring

Maintenance-Free: Automatically performs daily, monthly and six-month extensive self-checks of all main components: battery, internal electronics, energy charge and disarm, shock and ECG calibration systems. Daily testing data are stored by the device as text file (named AED1LOG) easily readable by any computer.
AED runs further tests after each battery insertion as well as every time the device is turned on.
A visual cue (green/red status indicator) provides effective alert to users whether AED is in working order and ready for a rescue.

Service Mini-Screen: In standby the mini LCD screen displays a check mark confirming AED is ready for use and a battery gauge informing about the residual charge. Will run error codes in faulty conditions.

Helpful Menu: 3 buttons for navigating the software menu to set up device at user leisure: adjust the local date or time, adapt the screen or volume to ambient lights and noises, exclude the microphone while recording events, select a different language, print out the ECG files or simply get information on device and battery.

CPR Coaching: More instructive voice and text prompts guide user through rescue. A built-in metronome assist responder during the CPR providing audio cues for the appropriate number and rate of chest compressions.

Adult / Child Capability: Can be used on patients of any age with Adult or Pediatric proper electrodes. Device senses when Pediatric pads are installed and automatically adjusts to use a more appropriate lower energy level (50J).

DEFIBRILLATOR

Operation:	AED Semi-Automatic ECG Monitoring capability
Energies:	Standard max 200J or Power max 360J
Waveform:	Adaptive BTE (biphasic truncated exponential) conforming to patient chest's impedance
Energy type:	Escalating from 50 to 360J
Protocols:	Various adult shock protocols available on request
Factory default:	Adult Standard escalating 150, 200, 200J Adult Power escalating 200, 250, 360J Pediatric (Standard or Power) 50J fixed
Charging time:	⩽9 seconds with a new and fully charged battery. Depleted battery will result in a longer charging time
Analysis time:	EN 60601, from 4 to 15 seconds
Impedance:	20-200 ohms
Sensitivity:	EN 60602-2-4 (AHADB, MITDB source), 97%
Specificity:	EN 60602-2-4 (AHADB, MITDB source), 99%
Controls:	ON/OFF, Shock button, 3 touch to surf the Menu
Indicators:	Status LED indicator informing on device condition Battery gauge with remaining capacity rate Audible alerts and text display with service alarms
Upgradeable:	Can be upgraded in the field through a USB cable or a removable card whenever protocols change

ECG MONITORING

Operation:	Through defibrillation pads or standard ECG electrodes attached to a separate 2-Lead patient monitoring reusable cable SAV-C0017
ECG Size:	Automatic gain controlled by the display
Heart Rate:	30-300 bpm
Sweep Speed:	25 mm/sec

5.7" TFT Color Display

the most detailed and comprehensive screen provides valuable information to rescuers running text and interactive graphics in tandem with voice messages



ABOUT DEVICE:
a **battery gauge** with residual capacity
the indicator of **available memory** for recording
a notice if the **microphone** is active or OFF
the local **date and time**

ABOUT RESCUE:
the adult or child **protocol in use**
the **modality in use** (AED or ECG)
the **fibrillation** and **shock counts**
the elapsed **rescue time**
the **heart rate** (bpm)
the **impedance** (ohms)
the **ECG** waveform
a **touch/not touch** pictogram
a **charging bar graph** if device charges
the **energy level** to be delivered (joule)
a **CPR bar graph** as countdown
a **CPR cycles** count

BATTERY OPTIONS

Type:	Li-SOCI2 Disposable, code SAV-C0903
Autonomy:	250 complete rescue cycles (shocks at 200J and CPR) or 160 complete rescue cycles (shocks at 360J and CPR) or 24 hours ECG Monitoring for a new and fully charged battery (*)
Shelf-Life:	8 years when stored in its original packaging (*)
Standby-Life:	5 years once installed to AED, assuming one battery insertion test and daily self-tests but without switching AED on (*)
Type:	Li-Ion Accumulator (rechargeable), code SAV-C0011
Recharging time:	2,5 hours with the charger station code SAV-C0014 (*)
Autonomy:	200 shocks at 200J or 110 shocks at 360J or 14 hours in ECG Monitoring for a new fully charged battery (*)
Shelf-Life:	2,5 years or 300 charging cycles (*)

PADS OPTIONS

Type:	Disposable, pre-gelled and self-adhesive
Adult:	Preconnected code SAV-C0846 for patient >8 years or >25Kg 81 cm² conductive surface
Pediatric:	Code SAV-C0016 for patient from 1 to 8 years old or <25Kg 31 cm² conductive surface
Cable lenght:	120 cm
Shelf-Life:	30 months

EVENT RECORDING

Internal memory:	1Gbit (128 MB)
Memory capacity:	6 hours of audio, ECG and event
Optional memory:	Removable SD card. Length of storage depends on card capacity: a 2GB card records up to 100 hours
Data recording:	"AED1LOG" text file with detailed self-test activity "AEDFILES" with complete recorded events
Event review:	"Saver View Express" data management software

PHYSICAL

Size:	26,5 x 21,5 x 7,5 cm
Weight:	2,30 kg with disposable battery 2,45 kg with rechargeable battery

ENVIRONMENTAL

Operating temperature:	0º C to 55º C
Storing/Shipping temperature:	-35º C to 60º C (without battery)
Humidity:	0% to 95% relative humidity non-condensing
Sealing (IP Protection):	IEC 60529 class IP54; slash proof, dust protected
Shock/Drop Abuse Endurance:	IEC/EN 60601-1 clause 21; 1 meter drop, impact, force, rough handling, mobile tolerance
Electrostatic Discharge:	EN 61000-4-2
Electromagnetic Compatibility:	EN 60601-1-2; Emission, Immunity
Electrical Protecion:	EN 60601-1 class I type BF / CF
EC Directive:	Class IIb

(*) Temperature at 20º C

MODEL NUMBERS

Code SVD-B0004:	Standard Version with maximum energy at 200J
Code SVD-B0005:	Power Version with maximum energy at 360J

CONFIGURATION OPTIONS (Box Contents)

Conf-Norm:	Standard Basic Configuration (adult pads, disposable battery, carrying case)
Conf-Rech:	Rechargeable Configuration (adult pads, accumulator, charger station, carrying case)
Conf-Print:	Print Ready Configuration (adult pads, disposable battery, carrying case, IrDA port and thermal printer)
Conf-Rech/Print:	Rechargeable & Print Ready Configuration (adult pads, accumulator, charger station, carrying case, IrDA port and thermal printer)

6 YEARS WARRANTY

Manufactured in Italy

IMQ mark for Safety & Quality

CE 0051

Saver One P®

the handy PRO AED

SAVER ONE P is a tough, small and lightweight Defibrillator easy to carry and use anywhere and able to act as an AED or a Manual Defibrillator or a Basic Cardiac Monitoring device.

HIGHLY FLEXIBLE AND VERSATILE WITH ADVANCED CAPABILITIES

AED per default, reliable for any BLS rescuer, can be easily switched in a Manual Defibrillator giving to ALS responders the best decision-making control for a manual shock timing or an electric cardioversion (synchronised shock).

To meet ALS professionals, SAVER ONE P has been designed with all advanced key features to make fast and effective defibrillation everywhere and in any circumstance, even the hardest and has been equipped with a new widely manageable software program which gives users the total control of device to suit their needs.

Practical and flexible with Advanced PBLS feature enabling healthcare providers to use the 15:2 CV ratio when performing a Pediatric Basic Life Support, as required by Guidelines if more than one rescuer with a duty to respond.

Supreme graphical user interface and new tools to have **total control** of the defibrillator

Biphasic **escalating energy** from 50 to 360J

Slight yet solid with long-lasting battery options to ensure the **best outdoor and mobile use**

Functionality guaranteed by daily self-test

Wider connectivity with removable card, USB and IrDA Port optional with Print Configuration

Unique features combined with available configurations give rise to exclusive devices

Meet AHA/ERC 2010 Guidelines

AED
ECG Monitoring
MANUAL Override

Saver One P®

Maintenance-Free: Automatically performs daily, monthly and six-month extensive self-checks of all main components: battery, internal electronics, energy charge and disarm, shock and ECG calibration systems. Daily testing data are stored by the device as text file (named AED1LOG) easily readable by any computer.
AED runs further tests after each battery insertion and every time device is turned on.
A visual cue (green/red status indicator) provides effective alert to users whether AED is in working order and ready for a rescue.

Service Mini-Screen: In standby the mini LCD screen displays a check mark confirming AED is ready for use and a battery gauge informing about the residual charge. Will run error codes in faulty conditions.

Entirely Discretionary: 6 push-buttons allowing users to get the total control of defibrillator while in use: select the best modality, Manual Synchronous or Asynchronous or simply AED, to treat SCA according to events, take decision for shock anytime by choosing the right energy level to be delivered at each shock and get the device charged and ready to shock whenever needed or even disarm it in case defibrillation is not more required.
After shocks, the heart rhythm rate can be watched over using the same defibrillation pads or, in case of longer monitoring, by connecting standard ECG electrodes to a separate optional reusable cable.
Each step is conducted with the appropriate running features selected and set up in the device software by users.

Adult / Child Capability: Can be used on patients of any age with Adult or Pediatric proper electrodes. Device senses when Pediatric pads are installed and automatically adjusts to use a more appropriate lower energy level (50J).

DEFIBRILLATOR

Operation:	AED Semi-Automatic (default) ECG Monitoring Manual Asynchronous or Synchronous (used to convert atrial or ventricular tachyarrhythmias)
Energies:	Standard max 200J or Power max 360J
Waveform:	Adaptive BTE (biphasic truncated exponential) conforming to patient chest's impedance
Energy type:	Escalating from 50 to 360J
AED Protocols:	Adult Standard escalating 150, 200, 200J Adult Power escalating 200, 250, 360J Pediatric (Standard or Power) 50J fixed (AED adult shock protocols can be customized)
Manual Protocol:	Selected by users from 50 to 360J. For electric cardioversions (in Synchronous mode) the shock is synchronised to occur with the R wave of the ECG.
Energy Display:	Screen provides the energy to deliver both in Manual mode or in AED mode
Charging time:	⩽9 seconds with a new and fully charged battery. Depleted battery will result in a longer charging time
Analysis time:	EN 60601, from 4 to 15 seconds
Impedance:	20-200 ohms
Sensitivity:	EN 60602-2-4 (AHADB, MITDB source), 97%
Specificity:	EN 60602-2-4 (AHADB, MITDB source), 99%
Controls:	ON/OFF, Shock button, 3 touch to surf the Menu, 3 keys for: select energy, charge device or disarm
Indicators:	Status LED indicator informing on device condition Battery gauge with remaining capacity rate Audible alerts and text display with service alarms
Upgradeable:	Can be upgraded in the field through a USB cable or a removable card whenever protocols change

ECG MONITORING

Operation:	Through defibrillation pads or standard ECG electrodes attached to a separate 2-Lead patient monitoring reusable cable SAV-C0017
ECG Size:	Automatic gain controlled by the display
Heart Rate:	30-300 bpm
Sweep Speed:	25 mm/sec

5.7" TFT Color Display

the most detailed and comprehensive screen provides valuable information to rescuers running text and interactive graphics in tandem with voice messages

ABOUT DEVICE:
a **battery gauge** with residual capacity
the indicator of **available memory** for recording
a notice if the **microphone** is active or OFF
the local **date and time**

ABOUT RESCUE:
the adult or child **protocol in use**
the **modality in use** (AED, ECG or Manual)
the **fibrillation** and **shock counts**
the elapsed **rescue time**
the **heart rate** (bpm)
the **impedance** (ohms)
the **energy level** to be delivered (joule)
a **touch/not touch** pictogram
the **ECG** waveform
the **R wave** detection in Manual Synchronous
a **charging bar graph** if device charges
a **CPR bar graph** and cycles countdown



BATTERY OPTIONS

Type:	Li-SOCI2 Disposable, code SAV-C0903
Autonomy:	250 complete rescue cycles (shocks at 200J and CPR) or 160 complete rescue cycles (shocks at 360J and CPR) or 24 hours ECG Monitoring for a new and fully charged battery (*)
Shelf-Life:	8 years when stored in its original packaging (*)
Standby-Life:	5 years once installed to AED, assuming one battery insertion test and daily self-tests but without switching AED on (*)
Type:	Li-Ion Accumulator (rechargeable), code SAV-C0011
Recharging time:	2,5 hours with the charger station code SAV-C0014 (*)
Autonomy:	200 shocks at 200J or 110 shocks at 360J or 14 hours in ECG Monitoring for a new fully charged battery (*)
Shelf-Life:	2,5 years or 300 charging cycles (*)

PADS OPTIONS

Type:	Disposable, pre-gelled and self-adhesive
Adult:	Preconnected code SAV-C0846 for patient >8 years or >25Kg 81 cm² conductive surface
Pediatric:	Code SAV-C0016 for patient from 1 to 8 years old or <25Kg 31 cm² conductive surface
Cable lenght:	120 cm
Shelf-Life:	30 months

EVENT RECORDING

Internal memory:	1Gbit (128 MB)
Memory capacity:	6 hours of audio, ECG and event
Optional memory:	Removable SD card. Length of storage depends on card capacity: a 2GB card records up to 100 hours
Data recording:	"AED1LOG" text file with detailed self-test activity "AEDFILES" with complete recorded events
Event review:	"Saver View Express" data management software

PHYSICAL

Size:	26,5 x 21,5 x 7,5 cm
Weight:	2,30 kg with disposable battery 2,45 kg with rechargeable battery

ENVIRONMENTAL

Operating temperature:	0° C to 55° C
Storing/Shipping temperature:	-35° C to 60° C (without battery)
Humidity:	0% to 95% relative humidity non-condensing
Sealing (IP Protection):	IEC 60529 class IP54; slash proof, dust protected
Shock/Drop Abuse Endurance:	IEC/EN 60601-1 clause 21; 1 meter drop, impact, force, rough handling, mobile tolerance
Electrostatic Discharge:	EN 61000-4-2
Electromagnetic Compatibility:	EN 60601-1-2; Emission, Immunity
Electrical Protecion:	EN 60601-1 class I type BF / CF
EC Directive:	Class IIb

(*) Temperature at 20° C

MODEL NUMBERS

Code SVP-B0006: Standard Version with maximum energy at 200J
Code SVP-B0007: Power Version with maximum energy at 360J

CONFIGURATION OPTIONS (Box Contents)

Conf-Norm:	Standard Basic Configuration (adult pads, disposable battery, carrying case)
Conf-Rech:	Rechargeable Configuration (adult pads, accumulator, charger station, carrying case)
Conf-Print:	Print Ready Configuration (adult pads, disposable battery, carrying case, IrDA port and thermal printer)
Conf-Rech/Print:	Rechargeable & Print Ready Configuration (adult pads, accumulator, charger station, carrying case, IrDA port and thermal printer)

6 YEARS WARRANTY

Manufactured in Italy

IMQ mark for Safety & Quality

CE 0051

SAVER ONE AED Series
supplies and accessories

Training Solutions

Saver One T Basic (code SVT-B0008)
Saver One T Advanced (code SVT-B0008A)

A smart and easy-to-use AED Trainer providing realistic training for many responders simultaneously.
Designed to meet needs of any instructor, it helps your responders learn to use defibrillators in simulated sudden cardiac arrest episodes for an extremely realistic training experience. A non-shocking unit that follows the 1, 2, 3-step operations of the Saver One defibrillator and guides responders, with voice prompts in various languages, from ECG analysis until shock and CPR. It is pre-configured with 10 realistic training scenarios manageable from distance with a wireless remote control and is equipped with a rechargeable battery which allows a 20 hours of continuous operating.

Both SAVER ONE T Versions come equipped with one set of Adult and Pediatric reusable training pads, a remote control, an accumulator with its charger, a quick reference card, an user manual and a carrying case.

The Advanced version provides to instructors 4 extra scenarios which can be fully customized via personal computer, once connected to AED Trainer with USB cable, using a dedicated software.

CPR Manikin
(code MAN-B0608)

Half-Body Training Manikin for Cardiopulmonary Resuscitation Practice with acoustic indicator for the correct deepness of compressions.

Composed of a jointed and removable head, an openable torso enclosing a lung bag and its valve, a knob on the back with three different selections, Adult, Child or Neutral, corresponding to three kinds of manikin resistance to compressions.

The articulated head allows inflating lungs only if the head is in the correct position.

ECG Monitoring & Data Management

2-Lead ECG Cable
(code SAV-C0017)

Suitable for SAVER ONE D and SAVER ONE P Defibrillators when used in ECG Monitoring mode. The alternative to pads in case of long-term monitoring to be connected to standard ECG electrodes.

Thermal Printer
(code SAV-C0018)

Works with SAVER ONE D and SAVER ONE P Defibrillators optioned with the Print Ready Configuration (Conf-Print).
Those are equipped with IrDA Port and therefore are able to communicate with this external thermal printer.
Data saved into device can be selected from the menu and print it out as ECG format complete with case details.

2GB SD Card
(code SAV-C0907)

This removable card holds approximately 100 hours of events, ECG information and voice recording.
One card can hold data from multiple cases.
A flash data card reader enables data transfer from the card to a personal computer for use with the Saver View Express data management software.

Saver View Express
(code SAV-C0019)

Saver View Express is a comprehensive data management tool for the most demanding professional allowing to view and manage on your PC patient data downloaded from defibrillators. With fully detailed data screen to record every aspect of the treatment, including response times, interventions, and rescuer observations.

Fast Access Solutions

AIVIA «S»
Basic Mounted Cabinet
(code SAV-C0836)

Designed for an indoor use, combining strenght and lightness with a polycarbonate cover and an ABS chassis.
Access to AED is protected by coated seals.
The front offers clear pictograms with the chain of survival and instruction for use.

Weight: 1,5 kg.
Dimensions (HxWxD): 400x341x198 mm

Wall Mount Bracket
(code SAV-C0911)

Composed of metal material. Specifically designed for housing a SAVER ONE Defibrillator hold in its original carrying case.

Weight: 1,37 kg.
Dimensions (HxWxD): 230x255x155 mm

Carrying Case
(code SAV-C0916)

Semi-Rigid, for a reliable protection and transport of Saver One Defibrillators.
Accessories and spare batteries can be stored in its inside compartments.
Made of special shockproof and splashproof material.
Zipper opening and "D" ring to hook from the back.

AIVIA 100
Alarmed Mounted Cabinet
(code SAV-C0028)



Ergonomic with no sharped corners.
Made of ABS and polycarbonate.
Access protected by plastic seals.
Internal grip strap to hold AED.
Sensor for automatic day/night light (when dark the compartment lits up if opened).
Opening the hood automatically triggers a visual alarm (flashing red LED) and an audio signal (hooter type: two tones 95 dB).

Weight: 3,5 kg.
Dimensions (HxWxD): 580x380x220 mm

Advanced Cabinets

AIVIA Family offers several combinations for the protection of AEDs even outside and/or for a complete surveillance.

The AIVIA 200 Series gives an outdoor protection from dust, humidity, rain, cold, etc.

The AIVIA 300 Series is able to protect and monitor AEDs giving a complete overview of their operating status.

Simulator / Tester

Smart Simulator S1
(code SSS-B0009)

This equipment can be used for a complete operating test of Saver One Defibrillators.
It comes with a dedicated cable to be plugged to any Saver One AED in order to let it run as it was a real lifesaving treatment.
Able to simulate several ECG rhythms (VF, VT, NSR, Asystole, etc.) and display the energy level discharged, up to 360J.

Connecting Cable
(code SAV-C0158)

Spare connecting cable for Smart Simulator S1.

the importance of AEDs....

Sudden Cardiac Arrest is a leading cause of death among adults in the world, claiming one life each two minutes. SCA is unpredictable and can strike anyone, anywhere at anytime !
Out-of-hospital SCA takes more lives than cancer, AIDS, Alzheimer, diabetes and whatever other disease or accidents. That's a life-threatening condition and when it happens only 10% survive. But SCA can be reversed if treated in time: An early CPR (to buy time) and a timely defibrillation (to restart heart) within 4-5 minutes from SCA can produce survival rates up to 70%.

AED is a key link in the Chain of Survival.

Availability and easy access to AEDs should be increased in all public areas where groups of people congregate or where EMS response time may be slowed, as well as AEDs should be used by any motivated bystander, regardless of training.

WORKPLACES

SCA is common in the general population, including those of working age and can be life-threatening, so it's sensible to consider what you would do if one of your employees or visitors suffered one. Deployment of AEDs in the workplaces to save lives is always recommended by any work health and safety organisation because the chances of surviving a cardiac arrest are increased if emergency treatment is given as soon as possible.

SCHOOLS

Every day, millions of students around the world are partecipating to physical activities such as basketball, football, volleyball or just at their gym class. Heart desease tends to go undetected and often manifest itself only during physical activities. Schools should be equipped with AEDs because in the event of SCA a quick response and the early defibrillation are critical to improving the chances of survival.

SPORTS

Life of sports men, no matter the discipline practiced, is daily marked by many physical and psychological sacrifices with the goal to increase performances for success: hours and hours of hard exercises, very few distractions and occasional leisures, stress and performance anxiety. However, there is a challenge that even the most prepared and coached athlete may not exceed: sudden cardiac arrest.

In Italy AED is mandatory for any sports team, no matter whether professional, semi-professional or just amateur.

everyday everybody everywhere

SaverOne
is Official Supplier to:

ACSI Associazione Centri Sportivi Italiani
Federazione Italiana Pallavolo
Confsport Italia
Federazione Italiana Nuoto

COMMUNITIES

AEDs are portable computerised devices safe and easy to use even without any formal training. However, training is recommended to provide a level of confidence and a speedy response in emergency situations. Governments should strongly advocate for PAD (public access defibrillation) programs that place automatic external defibrillators throughout communities and provide trainings in CPR and the use of AEDs to volunteers citizens. Most sudden cardiac deaths occur outside hospital then with more AEDs in the community, inhabitants become active part of the emergency response system, increasing the awareness and likelihood that first responders can save a life.

IN-HOSPITALS

AHA and ERC recommend the use of AED in-hospital. Infact the Guidelines say:
"AEDs should be considered for the hospital setting as a way to facilitate early defibrillation (a goal of <3min from collapse), especially in areas where staff have no rhythm recognition skills or where they use defibrillators infrequently.....Adequate numbers of staff should be trained to enable achievement of the goal of providing the first shock within 3min of collapse anywhere in the hospital".

ami.italia medical products